

CHINA

**DELLENT- YANGDONG** 

# Y4102D Yangdong Diesel Generator Water Cooled 50Hz Longer lifespan

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification: CE ISO
- Model Number:
- Minimum Order Quantity: 1\*
- Price:
- Packaging Details:
- Delivery Time:
- Supply Ability:
- DE-YD32 1\*20GP USD2000-4000 PLASTIC WRAP 30 DAYS FROM DEPOSIT RECEIVED 500 PCS PER MONTH



DELLEN

# **Product Specification**

• Name:

# Yangdong Diesel Generator Smartgen

- Controller Brand:
- Cooling System:
- Engine Brand:
- Noise Level:

• Rated Speed:

- Rated Frequency:
  - 15
- Highlight:

## 1500rpm Y4102D Yangdong Diesel Generator,

Water Cooled

YANGDONG

≤85dB(A)

50Hz

Yangdong Diesel Generator Water Cooled, Diesel Water Cooled Generator 50Hz

**Our Product Introduction** 

### 50Hz with Y4102D of Yangdong Diesel Generator

Product Introduce: Looking for reliable and high-quality diesel generators? Look no further than our Yangdong diesel generator series. We offer a range of models including 8kvato 71kva to meet your specific power needs.

### Application fields:

Our Yangdong diesel generators are known for their durability, fuel efficiency, and low maintenance requirements. With Yangdong engines at their core, these generators offer reliable power output that can be trusted for a range of applications. From backup power for homes and businesses to powering construction sites and events, our Y angdong diesel generators deliver the power you need when you need it.

### Advantage of our Yangdong diesel generator :

Yangdong diesel generator have a sturdy housing Longer lifespan Lower maintenance costs Lower noise level Faster delivery time Better team service Higher level technical support.

### Product parameters:

any interes	aing please contac	t with us to quote the			
	GenSet Model	DE-YD36	Туре	Silent(optional open)	
	Frequency (Hz)	50/60	Speed rpm	1500/1800	
	Phase	3	SRated voltage	230v/380v/400v/415v	
Details	Prime output	26.4kW/33kva(150 0rpm) 32kW/40kva(1800r	Standby output	29kW/36.3kva(1500rp m)	
		pm)		Silent(optional open) 1500/1800 230v/380v/400v/415v 29kW/36.3kva(1500r m) 35kW/44kva(1800rpr Water 2250*850*1050 75L 70DB-75DB Diesel Water-cooling 102 X 118 18.0:1 3.875 28 1VS4C H	
	Cylinder	4	Cooling system	Water	
	N.W (kg)	880	Size (L*W*H)mm	2250*850*1050	
	Fuel Con.(L/H)	9.2	Fuel capacity tank	75L	
	Running time (H)	8	Sound decibel	70DB-75DB	
	Brand	Yangdong			
	Model	Y4102D	Fuel	Diesel	
	Cylinder	4	Cooling system	Water-cooling	
	Cylider arrangemant	IN-LINE	Bore and Stroke(mm)	102 X 118	
	Cyle	4 Staoke	Compression ratio	18.0:1	
	Governor	Mechanical	Displacement(L)	3.875	
	Brand	Stamford, Leroy So	mer, Mecc Alte	29kW/36.3kva(1500rpm) 35kW/44kva(1800rpm) 35kW/44kva(1800rpm) Water 2250*850*1050 75L 70DB-75DB Diesel Water-cooling 102 X 118 18.0:1 3.875 228 1VS4C H IP23	
Details Genset Details Engine Details Alternator	Model	PI 044D/TAL-A40-C/LSA 40 VS0/ECP28 1VS4C			
	No.of bearings	1	Insulation class	Н	
	Wires	12	Ingress protection	IP23	
	Excitation system	Shunt	Volrage	±1%	
Optional si	ngle phase		•		
Delivery da	ate				
Custom	30 working days a	after payment			

### **Options:**

Canopy Design: including Denyo, Caterpillar, and Atlas, etc.

Alternator (AC): Stamford, Leroy Somer, Marathon, and Dellent brushless alternators TFW2 and YHG series. etc

<ul> <li>1)Brushless, 4 poles, rotation magne;</li> <li>2)IP21-23(NEMA1) enclose is standard for all industrial alternators;</li> <li>3)H class insulation system;</li> <li>4)AVR self-regulated, voltage regulation rate: ≤±1%;</li> <li>5)Simple installation and maintenance with easy access to terminals, rotating diodes and coupling bolts</li> <li>Control panel: Manual or digital control panel(with AMF function), varies brand for option; ATS can be option 1)Auto start when power goes out. Auto-stop when power comes back on;</li> <li>2)Worldwide technical support with programmable software download;</li> <li>3)Full online documentation;</li> <li>4)Trouble shooting symbols to assist owner on concerns with the generator.</li> <li>Type: silent type with canopy to reduce the noise level and Open frame without canopy for option</li> <li>Fuel tank: 8-10 hours in normal, can be custmised</li> </ul>	
Fuan Dellent Electric & Machinery Co., Ltd.	

NO.7, JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY, NINGDECITY, FUJIAN. CHINA

€ +8613706938606 Signature jennifer@dellent.com Biggardellentpower.com